



Introduction

The Atlona **AT-OME-EX-KIT** is an HDBaseT extender for video up to 4K/60 4:2:0, plus embedded audio, control, Ethernet, and USB over distances up to 330 feet (100 meters). Part of the Omega™ Series of integration products for modern AV communications and collaboration, the OME-EX-KIT is HDCP 2.2 compliant and extends IR, RS-232, and IP control signals. The integrated USB extension addresses the challenge of connecting between USB devices at remote locations, and is ideal for software video conferencing and touch or interactive displays. The OME-EX-TX transmitter includes a USB 2.0 host interface for a PC, plus two peripheral devices such as a speakerphone, microphone, or keyboard and mouse. The OME-EX-RX receiver provides two USB interfaces for devices such as a camera or display. The transmitter and receiver are available separately, for use with other Omega Series integration products⁽¹⁾.

Applications

- **Video Conferencing**

The OME-EX-KIT is ideal for soft codec and web-based conferencing applications, with the ability to integrate with a PC and speakerphone or microphone at a meeting table, and a camera or soundbar at the wall-mounted display.

- **Interactive displays**

The OME-EX-KIT can also provide AV and USB extension for a touch-enabled display, allowing remote PC control at a meeting table or other location.

Key Features

HDBaseT extender kit for HDMI, Ethernet, power, control, and USB up to 330 feet (100 meters)

- Extends HDMI up to 330 feet (100 meters) @ 1080p with CAT5e/6 or 4K/UHD using CAT6a/7 cable.
- Uses easy-to-integrate category cable for low-cost, reliable system installation.

USB 2.0 hub and extension over HDBaseT

- Transmitter features USB type-B interface for connection to a host PC, plus two USB type-A ports for peripheral devices such as a microphone or speakerphone. Receiver features two USB type-A ports for peripheral devices such as a camera or display.
- Provides an ideal USB integration solution for software video conferencing and other applications.

4K/UHD capability @ 60 Hz with 4:2:0 chroma subsampling

- Compatible with sources up to 4K/60 4:2:0 and 4K/30 4:4:4.
- Supports HDMI data rates up to 10 Gbps from PCs, media players, and Ultra HD Blu-ray players.

HDCP 2.2 compliant

- Adheres to latest specification for High-bandwidth Digital Content Protection.
- Allows protected content stream to pass between authenticated devices.

Transmitter powered by receiver via PoE (Power over Ethernet)

- Industry standard IEEE 802.3af PoE for transmitter is supplied by receiver over HDBaseT.
- Allows convenient transmitter installation at a table or other remote location, without the need for local AC power.

Low-profile, 1 inch (25 millimeter) high quarter rack-width enclosure

- Easy installation into racks and confined spaces.
- Keeps devices out-of-sight when placed in public spaces.

Award-winning 10 year limited product warranty

- Ensures long-term product reliability and performance in residential and commercial systems.
- Specify, purchase, and install with confidence.

Specifications

| Video | |
|--------------------|---|
| HDMI Specification | HDMI 2.0, HDCP 2.2 |
| TMDS Clock | 300 MHz |
| UHD/HD | 4096×2160(DCI)@60 ⁽²⁾ /30/24 Hz, 3840×2160(UHD)@60 ⁽²⁾ /50/24/25/30 Hz, 1080p@23.98/24/25/29.97/30/50/59.94/60 Hz, 1080i@25/29.97/30 Hz, 720p@30/50/59.94/60 Hz |
| VESA | 2560×2048, 2560×1600, 2048×1536, 1920×1200, 1680×1050, 1600×1200, 1600×900, 1440×900, 1400×1050, 1366×768, 1360×768, 1280×1024, 1280×800 1280×768, 1152×768, 1024×768, 800×600, 640×480 |
| Color Space | YUV, RGB |
| Chroma Subsampling | 4:4:4, 4:2:2, 4:2:0 |
| Color Depth | 8-bit, 10-bit, 12-bit |

| Audio | |
|--------------|---|
| Pass-through | PCM 2Ch, LPCM 5.1, LPCM 7.1, Dolby® Digital, DTS 5.1, Dolby Digital Plus, Dolby TrueHD, Dolby Atmos®, DTS®, DTS-HD Master Audio™, DTS:X |
| Sample Rate | 32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz |
| Bit Depth | Up to 24-bit |

| USB | |
|-------------------|----------|
| Signal | 2.0 |
| Maximum Data Rate | 120 Mbps |

| Control | |
|---------|--|
| CEC | Pass-through |
| RS-232 | Pass-through from control system to sink device; supports baud rates from 2400 to 115200 |
| IR | Pass-through from control system to sink device |
| IP | Pass-through from control system to sink device up to 100 Mbps over HDBaseT |

| Connectors | |
|-------------|---|
| HDMI IN | 1 - Type A, 19-pin female (transmitter) |
| HDMI OUT | 1 - Type A, 19-pin female (receiver) |
| FW | 1 - mini-USB (transmitter / receiver) |
| HDBaseT IN | 1 - RJ45 (transmitter) |
| HDBaseT OUT | 1 - RJ45 (receiver) |
| HOST | 1 - USB Type-B (transmitter) |
| DEVICE | 2 - USB Type-A (transmitter / receiver) |
| LAN | 1 - RJ45, 10/100 Mbps (transmitter / receiver) |
| RS-232 / IR | 1 - captive screw, 4-pin (transmitter / receiver) |
| DC 48V | 1 - 3-pin DIN (receiver) |

| Indicators and Controls | |
|-------------------------|-----------------|
| PWR LED indicator | 1 - LED, green |
| LINK LED indicator | 1 - LED, yellow |

| Resolution / Distance | 4K/UHD - Feet / Meters | | 1080p - Feet / Meters | |
|-----------------------|------------------------|-----|-----------------------|-----|
| HDMI IN/OUT | 15 | 5 | 30 | 10 |
| CAT5e | 295 | 90 | 330 | 100 |
| CAT6/6a/7 | 330 | 100 | 330 | 100 |

| Power | |
|----------------------------------|--|
| Consumption | 32.35 W |
| USB Power | 2.5 W per USB device interface |
| External Power Supply (Receiver) | Input: 100 - 240 V AC, 50/60 Hz Output: 48 V, 0.83 A DC |
| Safety | CE, FCC, cULus |

| Environmental | |
|-------------------------|----------------------------------|
| Operating Temperature | 0° to 122° F 0° - 50° C |
| Storage Temperature | -4° to +140° F -20° to +60° C |
| Operating Humidity (RH) | +20 to +90%, non-condensing |

| Dimensions (H x W x D) | Inches | Millimeters |
|-------------------------------|--------------------|----------------|
| Unit (TX / RX) | 1.02 x 4.29 x 5.00 | 26 x 109 x 127 |
| Power Supply (AT-PS-48083-D3) | 1.42 x 1.81 x 4.41 | 36 x 46 x 112 |

| Weight | Pounds | Kilograms |
|------------------|--------|-----------|
| Device (TX / RX) | 0.89 | 0.41 |

| Certification | |
|---------------|---------------|
| Device | CE, RoHS, FCC |

- (1) Both the AT-OME-EX-TX and AT-OME-EX-RX and not compatible with the AT-UHD-HDVS-300 system for extending USB.
 (2) Only supports 4:2:0.

Copyright, Trademark, and Registration

© 2021 Atlona Inc. All rights reserved. “Atlona” and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI licensing Administrator, Inc.



Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.



For DTS patents, see <http://patents.dts.com>. Manufactured under license from DTS, Inc. DTS, the Symbol, DTS and the Symbol together, and Digital Surround are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).