

# PressIT Sistema Wireless para presentaciones

Sistema de Presentación Plug & Play  
Sencilla solución de colaboración plug & play



## KEY FEATURES

- Para señales audiovisuales de PC, dispositivos iOS/Android y otros dispositivos móviles
- Dos tipos de receptores: Todas las pantallas y proyectores son compatibles con descodificador, placa SDM para pantallas SQ1 y SQE1
- Compatible con el control de comandos HDMI-CEC, funcionamiento enlazado con los dispositivos compatibles con CEC
- Hasta 4 fuentes de visualización simultáneas y hasta 32 conexiones simultáneas del transmisor
- No es necesario instalar ningún software ni controladores, ni realizar ninguna conexión en red

<p><b>Destinatario</b> (Descodificador)</p>	<p><b>Transmisor</b> (HDMI/USB)</p>	<p><b>Estuche del transmisor</b></p>	<p><b>Receptor (SDM)</b></p>	<p><b>Transmisor (USB-C)</b></p>

## SPECIFICATIONS

<b>Product</b>	Wireless Presentation System Basic Set
<b>Max. output resolution / Framerate</b>	Receiver : 1920 x 1080/60p,3840 x 2160/30p (max.)
<b>Max. input resolution / Framerate</b>	Transmitter : 1920 x 1080/60p (max.)
<b>Number of simultaneous connections</b>	32
<b>Number of sources simultaneous on screen</b>	4
<b>Data Rate   Wired</b>	10/100/1000 (Mbps)
<b>Data Rate   Wireless</b>	Receiver : 867 Mbps (max.) Transmitter : 433 Mbps (max.)
<b>Frequency Band</b>	5 GHz (5180 MHz to 5240 MHz)
<b>Wireless Communication Standard</b>	Receiver : IEEE802.11/a/n/ac Transmitter : IEEE802.11ac
<b>Seguridad</b>	WPA/WPA2
<b>Reach (Max distance between transmitter and receiver)</b>	30 m (When the line of sight/wave conditions are good)
<b>Connection terminal</b>	Receiver : HDMI/USB-A (female)/RJ45 (LAN) Transmitter : HDMI/USB-A (female)/USB-A (male)
<b>Power Requirements</b>	Receiver : DC 5 V/2 A Transmitter : DC 5 V/0.9 A
<b>Power consumption (During image display)</b>	Receiver : 10 W Transmitter : 4.5 W
<b>Temperature   Operating</b>	Temperature: 0 °C to 35 °C (32 °F to 95 °F)
<b>Temperature   Storage</b>	Temperature: -20 °C to 60 °C (-4 °F to 140 °F)
<b>Dimensiones (AnxAIxP)</b>	Receiver : 120 x 26 x 81 mm (4.71" x 1.03" x 3.19") <sup>①</sup> Excluding antenna part <sup>②</sup> Transmitter : 50.8 x 19.5 x 73.2 mm (2.00" x 0.80" x 2.86") (Excluding cables) Case : 151.3 x 41.6 x 198.0 mm (5.96" x 1.64" x 7.8")
<b>Peso</b>	Receiver : Approx. 181 g / 0.4 lbs Transmitter : Approx. 110 g / 0.3 lbs Case : Approx. 315 g / 0.7 lbs

URL: <https://business.panasonic.es/sistemas-visuales/sistema-de-presentaciones-inalambricas>

## CONTACT

Web: <https://business.panasonic.es/sistemas-visuales/contact-us>