

# VL10 BEAMWASH

Date: \_\_\_\_\_

Type: \_\_\_\_\_

Firm Name: \_\_\_\_\_

Project: \_\_\_\_\_

The Vari-Lite VL10 BEAMWASH packs class-leading power, dynamics and personality into a compact, fast-moving body. Producing 28,000 lumens and weighing just 33 kg, it's brighter, lighter and more versatile than any comparable fixture. A suite of dynamic effects offers endless creative possibilities, from the dual overlapping prisms to the aperture wheel, rotating gobo wheel and stunning aerial effects from the exclusive new VL\*FX wheel. An internal frost can soften effects, while a heavy frost lens creates a strong, even wash. VL's enhanced CYM system and fixed color wheel offer designers a full palette, from the subtlest hues to the deepest reds and blues.



- Exclusive new 25R Platinum 550 W lamp.
- Narrowest beam reduction 0.7°.
- The brightest fixture in its class 28,000 lumen of output (640,000 lux @ 10m).
- Large impact stage presence from a 180 mm front lens, a look only usually associated with much larger fixtures.
- Ultra compact – 704 x 501 x 320 mm - 33kg.
- Image softening, variable 1° frost.
- Endless color options, CYM color mixing and fixed color wheel.
- Wide zoom range – 2.2° to 48°.
- Exclusive VL\*FX animation wheel system, that creates dynamic new projected and mid-air effect.
- Feature loaded for mid-air effects, 4 beam reduction and 8 beams shapes fixed apertures gobos and 8 fully rotating gobos.
- Dual overlay prism system.
- Ready to tour, ships complete with foam shell insert.

For detailed product information, please refer to the Product Guide at <https://www.vari-lite.com/global/products/vl10-beamwash>



# VARI\*LITE

# Specifications

Due to continuous improvements and innovations, specifications may change without notice.

## Source

Lamp	Philip 25R Platinum
Source Max Power Consumption	550 W
Source CCT	8000 K
Dimming	Mechanical blades 16-Bit
Dimmer Curves	Square Law (Default), Linear, S -Curve
Strobe Speed	0 - 30Hz
Strobe Modes	Continuous, Random, Random Sync

## Optical Performance

Lens Size	180 mm (7.0 in)
Zoom Range	2.2 - 48°
Zoom Control	Motorized 16-Bit
Focus	Motorized 16-Bit Control
Output Lumens	28000
Output CCT	7500 K
CRI RA	84

## Color System

Subtractive Color Mixing	CMY Glass Flags
Color Mixing Control	CMY 8-bit
Fixed Color Wheel	10 Colors + Open
Color Wheel Effects	Split Colors, Color Wheel Spin, and Shake

## Imaging

Effects Prism	8 Facet Round
Effects Prism	6 Facet linear
Prism Features	Index/Rotation, MegaStep, Dual Overlay
Beam Softening 1	Variable control - Light Frost
Beam Softening 2	Heavy Wash Frost

## Electrical

Max output Power Consumption	950 W
Power Connection	Neutrik TrueOne - Input only Power cable not included - input connector only
Input Voltage	100–240 VAC, 50 / 60 Hz

## Data

Supported Protocols	DMX (RDM), ArtNet
DMX Modes	
16-Bit Enhanced	41 Channels
16-Bit	36 Channels
Clone Mode	31 Channels
Data Connections	5 - PIN XLR Input & Thru, RJ45 Input
Manual Preset Mode	Advanced Feature local control
FollowSpot Mode	Manual FollowSpot Operation

## Noise Level / Fan Control

Fan Mode	Continuous (On) / Auto Ramping
Cooling System Type	Forced Air

## Mounting


Hanging Type	2 x VL Hook Rails
Fixture mounting/Hanging orientation	Hanging - Floor - Side *See user manual for side hang guidance and restrictions
Secondary Safety Wire Point	1 x Safety point located on underside of upper enclosure Safety Wire not included

## Photometrics and IES Files

2.2° Beam @ 10 m / 32.8ft	640,000 lux (59,458 fc)
2.2° Beam @ 15 m / 49 ft	280,000 lux (26,013 fc)
2.2° Beam @ 20m / 65.6 ft	160,000 lux (14,865 fc)
44° Beam @ 10 m 32.8ft	2,300 lux (214 fc)
44° Beam @ 15 m / 49ft	980 lux (91 fc)
44° Beam @ 20m / 65.6 ft	555 lux (52 fc)

For IES files and photometric reports, please refer to the product page:  
<https://www.vari-lite.com/global/products/vl10-beamwash>

# Dimensions




## Physical

Construction	Superstructure made of Aluminum, and steel metal plates, Covers self-extinguishing fire retardant ABS PC (V0 class)
IP Rating	IP20
Standard Finish	Black
Dimensions	501 x 704 x 320 mm (20.0 x 28.0 x 13.0 in)
Fixture Weight	33.0 kg (73.0 lb)
Operating Temperature	0-40°C (32-104°F)

## Certification and Safety

Approbations	CE, ETL, UL, FCC CSA, RoHS, ISO 9001
--------------	--------------------------------------


### Gobo Wheel 1



### Gobo Wheel 2



### VL\*FX Wheel



## Gobo and Effect Wheels

Gobo Wheel 1	Fixed 12 + Open
Gobo Wheel 2	Rotating/Indexable 8 + Open Interchangeable
Gobo Diameter / Thickness	14 mm x 0.5 mm
Image Size	8 mm
VL*FX Animation	5 + Open
Gobo Diameter / Thickness	35 mm x 1.1mm
Image Size	35mm
Gobo Wheel/VL*FX Features	MegaStep, Twist, Shake, Wheel Spin

# Luminaire and Accessories

Product type	Order Code
VL10 BEAMWASH 550W 25R Platinum Lamp, foam shell insert, hanging rails, and TrueOne power input connector	20.1810.0001
Accessories	
VL10 BEAMWASH, Gobo carrier - with magnet w/gobo retaining spring	5.01.02.01.0449-A
VL10 Gobo carrier	5.01.02.01.0450-A
VL10 BEAMWASH, Gobo carrier - no magnet ,c/w gobo retaining spring	
GT Truss Rail	22.9708.0835
VL GT Truss hook rail per rail (Fits VL4000,VL6000,VL2600, VLZ, and VL10)	



© 2023 Signify Holding. All rights reserved. All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

07/17/2023

Vari-Lite  
<https://www.vari-lite.com/global/products/M10-beamwash>